



# J1D-02

Handheld 1D Imager Scanner

## Features

- ☆ Reading smart phone screen
- ☆ Auto-sense function
- ☆ Energy Conservation
- ☆ Durable Constuction
- ☆ Cost-effective Solution



## Specifications

General	
Interface	RS232 / USB
Symbologies	UPC / EAN / JAN, UPC / EAN with Supplementals, UCC/ EAN 128, Code 39, MSI, Code 11, Code 39 Full ASCII, Code 128, Code 128 Full ASCII, Codabar, Code 93, Discrete 2 of 5, RSSvariants, Codabar, Chinese 2 of 5, Interleaved 2 of 5, etc.
Optical	
Resolution	4 mil
Image Sensor	1500 pixels CCD
Light Source	620nm red LED
Print Contrast	30%
Electrical	
Input	5V±5%
Power Consumption	250mW (typical)
Current	50mA (typical)
Environment	
Operating Temperature	-20~50°C
Storage Temperature	-40~60°C
Drop	2m
Sealing	IP54
Physical	
Weight	135g
Dimensions	160mm(L) x 90mm(W) x 65mm(H)
Housing Material	ABS + PC
Certifications	
Certifications	EN55022, EN55024, EN60950-1



浪塔科技有限公司

Lambda-Tek Company Limited