

# J2D-02

Handheld 2D Imager Scanner

## Features

- ☆ Reading smart phone screen
- ☆ Auto-sense function
- ☆ Outstanding Performance
- ☆ Durable Constuction
- ☆ Cost-effective Solution



## Specifications

General		
Interface		RS232 / USB-KB / USB-COM
Symbologies	1D	UPC-A, UPC-E, EAN-8, EAN-13, Code 128, Code 39, Code 93, Code 11, Interleaved 2 of 5, Matrix 2 of 5, Standard 2 of 5, Coda bar, MSI Plessey, RSS, Codabar, ISBN, ISSN, GS1 DataBar(RSS14)etc.
	2D	QR code, PDF417, DataMatrix, Aztec code, Maxicode, etc.
Optical		
Resolution	1D	4 mil
	2D	4 mil
Image Sensor		640x480 CMOS
Light Source		624nm LED
Print Contrast		25%
Electrical		
Input		5V±10%
Power Consumption		400mW (typical)
Current	Operating	80mA
	Idle	30mA
Environment		
Operating Temperature		-20~50°C
Storage Temperature		-40~60°C
Operating Humidity		5~95% RH (non-condensing/non-freezing)
Storage Humidity		5~95% RH (non-condensing)
ESD		N/A
Drop		2m
Sealing		IP54
Physical		
Weight		111g
Dimensions		160mm(L) x 90mm(W) x 65mm(H)
Certifications		
Certifications		CE, FCC, RoHS, IP54