

HONEYWELL 1900

Handheld 2D Imager Scanner

Features

- ☆ Outstanding Performance
- ☆ Ergonomic Design
- ☆ Durable Construction
- ☆ Great Symbolologies Compability



Specifications

General

Interface		RS232, USB, PS/2
Symbolologies	1D	Interleaved 2 of 5, Korea Post, China Post , Matrix 2 of 5, Codabar, MSI, NEC 2 of 5, Code11, Code128, Postal Codes, Code32, Code39, Code93, Straight 2 of 5, EAN13, JAN13, EAN8, JAN8, Telepen, GS1 DataBar, GS1-128, GS1 Emulation, Trioptic Code, UPC-A/E
	2D	PDF417, Micro PDF417, Micro QR, QR Code, Data Matrix, Aztec.

Optical

Resolution	1D	HD : 3 mil, SR : 5 mil, ER : 5mil
	2D	HD : 5 mil, SR : 6.7 mil, ER : 7.5mil
Image Sensor		838x640 pixels
Light Source		617nm Red LED
Print Contrast		20%

Electrical

Input		4~5.5V
Current	Operating	450mA
	Idle	90mA

Environment

Operating Temperature		0~50°C
Storage Temperature		-40~70°C
Operating Humidity		0~95% RH (non-condensing/non-freezing)
Storage Humidity		0~95% RH (non-condensing/non-freezing)
ESD		±15KV (air discharge); ±8KV (direct discharge)
Drop		1.8m
Sealing		IP41

Physical

Weight		147g
Dimensions		160mm (L) x 104mm (W) x 71mm (H)

Certifications

Certifications		FCC Class B, UL60950-1, CSA C22.2 No.60950-1-03, ICES-003, EC EMC CLASS B, EN55024, EN61000-3-2, EN61000-3-3, IEC 60950-1, IEC60825-1.
----------------	--	--



浪塔科技有限公司

Lambda-Tek Company Limited