



NLS-HR1580-BT

Wireless Handheld Linear Imager Scanner

Features

- ☆ Outstanding Performance
- ☆ Reliable Wireless Communication
- ☆ Powerful Data Editing Function
- ☆ Low Consumption & Great Compatibility



Specifications

General

Interface	RS232 / USB
Symbologies	Code 11 , Code 128, Code 39, GS1 128(UCC/EAN 128), AIM 128, ISBT 128, Codabar, Code93, UPC A, UPC E, Coupon, RSS, Plessy, GS1 Composite , EAN 8, EAN 13, ISBN/ISSN, Interleaved 25, Matrix 25, Industrial 25, ITF 6, ITF 14, Standard 25, China Post 25.

Optical

Resolution		4 mil
Image Sensor		2500 CCD
Light Source	Aiming	625nm Red LED
	Illumination	625nm Red LED
Print Contrast		25%

Electrical

Input	5V±5%
-------	-------

Environment

Operating Temperature	-20~60°C
Storage Temperature	-40~70°C
Operating Humidity	10~90% RH (non-condensing/non-freezing)
Storage Humidity	5~95% RH (non-condensing)
ESD	±8KV (air discharge); ±4KV (direct discharge)
Drop	1.5m
Sealing	IP42

Wireless

Radio Technology	Bluetooth 5.0 (communication distance up to 50m)
Battery	2200 mAh lithium-ion battery
Expected Charge Time	4 hours
Expected Battery Life	15 hours of continuous operation (scan once per 6 seconds)
Memory Capacity	≥15000 pieces Code 128 (20 byte of each Code 128)

Physical

Weight	217g
Dimensions	113.5mm(L) x 73.3mm(W) x 159.9mm(H)

Certifications

Certifications	FCC Part15 Class B, CE EMC Class B, RoHS
----------------	--



浪塔科技有限公司

Lambda-Tek Company Limited